



FILTRI

192 Filtro a Y

Adatti all'impiego in impianti idraulici, di riscaldamento, di condizionamento e aria compressa.
FILTRO A Y



MISURA	PRESSIONE	CODICE	IMBALLO
1/4" (DN 8)	20bar/290psi	1920014	20/140
3/8" (DN 10)	20bar/290psi	1920038	20/140
1/2" (DN 15)	20bar/290psi	1920012	20/140
3/4" (DN 20)	20bar/290psi	1920034	10/70
1" (DN 25)	20bar/290psi	1920100	8/48
1"1/4 (DN 32)	20bar/290psi	1920114	5/30
1"1/2 (DN 40)	20bar/290psi	1920112	2/18
2" (DN 50)	20bar/290psi	1920200	2/10
2"1/2 (DN 65)	16bar/232psi	1920212	1/7
3" (DN 80)	16bar/232psi	1920300	1/6
4" (DN 100)	16bar/232psi	1920400	1/2

CERTIFICAZIONI



CAPITOLATO

Attacchi filettati femmina/femmina e tappo d'ispezione.

Corpo in ottone.

Temperature minima e massima di esercizio: -20°C, 110°C in assenza di vapore.

Attacchi filettati ISO 228 (equivalente a DIN EN ISO 228 e BS EN ISO 228).

Grado di filtrazione: - da 1/4" a 2" 500µm; - 2"1/2, 3", 4" 800µm.

INGOMBRI

